

4Vie 3530

CS Italia s.r.l.



Optional su richiesta info@carrellispeciali.it 

General info	1.1	Manufacturer			CSI s.r.l.
	1.2	Model			4Vie 3530
	1.3	Drive			elettrico AC
	1.4	Operator type			a timone
	1.5	Load capacity	Q	t	3
	1.6	Load centre	c	mm	600
	1.8	Load distance to wheel axle	x	mm	780
	1.9	Wheelbase	y	mm	1780
	Weights				
2.1	Truck weight without battery			Kg	1600
Wheels and chassis					
3.1	Wheels				Poliuretano
3.2	Wheels size front			mm	300x100
3.3	Wheels size rear			mm	150x50
3.5	Number of rear/front wheels (x = Traction wheel)				1x/2+2
3.7	Rear wheelbase	b11		mm	2300
3.9	Overall width legs	ge		mm	2520
3.10	Inside width legs	gi		mm	2020
3.11	Legs height	h8		mm	255
Dimensions					
4.1	Tilt			°	-1/+2
4.2	Height mast lowered	h1		mm	2430
4.4	Lift height	h3		mm	3460
4.5	Height mast extended	h4		mm	4200
4.9	Height of tiller (min/max)	h14		mm	975/1535
4.15	Height forks lowered	h13		mm	50
4.19	Overall length	l1		mm	2785
4.20	Length to face of forks	l2		mm	1385
4.21	Overall width	b1		mm	1076
4.22	Forks dimensions	s/e/l		mm	45/120/1200
4.23	Carriage forks				FEM 3A
4.25	Overall forks width size	b5		mm	260-1970
4.31	Ground clearance			mm	40
4.34	Aisle width	ast		mm	2690
4.35	Turning radius	wa		mm	1970
Performance					
5.1	Travel speed with/without load			Km/h	3/6
5.2	Lifting speed with/without load			m/s	0.11/0.33
5.3	Lowering speed with/without load			m/s	0.5/0.2
5.8	Maximum gradeability with/without load			%	2/3
5.10	Service brake				elettrico
Motor					
6.1	Traction motor S2 60 min.			Kw	3
6.2	Lift motor S3			Kw	3
6.3	Battery				Piombo acido
6.4	Battery - voltage and nominal capacity			V/Ah	24V 420 Ah
6.5	Battery weight			Kg	320
Dim. batteria	Battery size			mm	1015/255/575
Other					
8.1	Traction control				elettronico
8.4	Noise level driver place				<70

